

Please collect the following information to use in the selection of pipeline shock, surge, & hammer prevention equipment.



Please first consider whether the addition of pressure vessels to your piping system, can be avoided completely.

A Can the need for pump start-up surge prevention be made un-necessary ?

1). To start a pump without a surge, start the pump slowly. If you specify a pressure that must not be exceeded

Liquid Dynamics will quote for working out how slowly you must start your pumps, for you .

2). Start as normal, but allow the flow to by-pass back to suction against a gradually increasing resistance of a slow closing valve in the bypass line. If you state the space available, and the pressure that must not be exceeded, -

Liquid Dynamics will quote the by-pass system for you.

B Can the need for valve closure shock prevention be made un-necessary ?

1). To close a valve without a shock, close the valve more slowly. When you specify a pressure that must not be exceeded,

Liquid Dynamics will quote for working out how slowly you must close your valve, for you.

2). Stop the flow going through the fast closing valve in the normal way, but first open another valve in a smaller line from a "T" immediately ahead of the fast closing valve, this line will be piped back to a point nearer to point of volume supply. State the space available and the pressure that must not be exceeded.

Liquid Dynamics will quote for determining the back-pass system dimensions for you.

C Can the need for pump shut-down back-flow hammer prevention be made un-necessary?

1). To stop a pump, without a back-flow hammer, slow the pump down gradually; or de-clutch the pump from its driver & allow the pump to spin down, while the inertia of the mass flowing away from the pump pulls liquid through the pump .

2). If you can not decouple the pump drive, then provide a "suck-by" circuit, allowing the void that is sucked out behind the liquid that continues to travel away from the pump, to be filled by sucking past the pump.

Liquid Dynamics will quote for establishing the dimensions of the "suck-by" circuit, for you.

When neither 1. nor 2 of A, B, C, above, "preventive methods" are possible, we can provide a list of companies who can provide vessels suitable for the duties established by a *ShockView* model of the data that you provide to LDi, as below.

Both ASME vessel code and the EU Pressure Equipment Directive require your full disclosure of all use parameters.

INFORMATION Req'd.	UNITS	LIQUID Examples.	Customer Guestimates from past.	Please mark :- U = From process log. V = Physics tables W= Guestimation
Liquid Density.	Grams per milliliter	Water	1.00	SG g/cm3
Specific Gravity	Grams per Cubic cm.	30% NaOH Solution	1.30	
SG @ System Temp.	Kg / Liter or g/cm3	Ammonia NH ₃	@ -30 C 0.68	
Liquid Viscosity @ System Temp.	Centipoise, cP	Water	1.00	Viscosity cP
		w/ absorbed CO ₂ 30% NaOH Solution	30.0	
		Ammonia NH ₃	0.35	
Compressibility, reduction in volume per unit change in pressure, @ system pressure & Temp.	parts of a Liter per Bar L/Bar Liters /Kg cm2	w/ absorbed air Water @ 10 Deg. C Pentene & Pentane+HFacid Ammonia NH ₃	50e-6 @ + 40 C 19.6e-5 11.389e-4	Compressibility L/Bar
Which is like saying that hot light hydrocarbons are like 98 Deg C water and are 4 x compressible than cold water, and the second example, liquid ammonia is 22 times more compressible than cold water.				
A Dynamic (dt) equation must be resolved, accurate Time figure is essential It has an exponential effect.	Pump run up time (For a positive displacement pump time for first 5% of a displacement) or valve closure time or pump run down Secs. ("Instantaneous" shall mean 0.01Sec., 10ms)	1450 motor 6"x4" Centrif. 6" Air actuated butterfly Diesel driven 24"x20" Cenrif. Meter stop valve (depending on size.)	2.0 Secs 1.0 Sec 5.0 Secs 0.05 to 0.300 Secs.	Time Secs
Bulk Modulus, Elasticity of pipe material	Pascalles Pa	Steel Concrete Plastic PVC	2e+11 4.2e+10 2.89e+9	Elasticity Pa.
Pipe Wall thickness mm	Millimeters	(Dilation of pipe wall combined & liquid compressibility determines shock reduction & frequency) "effective softness"		
Pipe Internal Diameter	Millimeters mm	mm	Force, Pressure at Pipe Inlet	Bar or Kg/cm2
Pipe Length	Meters (Feet x 0.305)	M	Pressure that Shock must not exceed.	Bar or Kg/cm2
Theoretical mass flow	Kilograms per second Kg/Sec. US GPM x 3.8 /60 x SG	Kg/Sec	Acceptable Materials of Construction	Metals Synthetic Rubbers Plastics
Frequency of any current vibration	Hertz, Hz.	Vapor pressure at suction temperature for item C2 above.		



LIQUID DYNAMICS INTERNATIONAL Inc.

Analysis, Diagnostics, Prediction by Software

Phone USA --910-270-2737 Color Fax --910-270-0320 UK (for EC) --44-161-442-6222 Color Fax --44-161-443-1486
Box 506 Hampstead NC 28443 www.liquid-dynamics.com Box 47, Stockport, SK3-0LH, UK